



PT 33LSC

LAMINATE • SLIT • CUT



Designed to meet the demands of the digital short run printer the PT 33LSC not only cuts to bleed for a finished product, but also has a variable size encapsulation mode. Choose your encapsulation width through the programming for 2-sided pouch lamination with a customizable border size. Remove the bottom roll with our convenient roll away feeder and perform true singled sided laminating without the need for a release liner. The easy to use external anti-curl lever ensures your single sided work will lay flat. The PT 33LSC boasts the highest film yield while in operation with only an 1/8" gap between sheets. Automatic setup, productive speeds and the efficient 2" vacuum pile feeder makes for a 'set it and forget it' laminating experience.

The PT 33LSC also has a foiling option, also known as foil sleeking. This embellishment method is the process of metallic foil adhering to an area layered by toner, producing unique beautiful finishes with ease.

FEATURES

Roller Pressure and Anti-Curl Settings



Foil Attachment



SPECIFICATIONS

Min Sheet Size

7" x 7" (17.78cm x 17.78cm)

Max Sheet Size

13 x 19.7" (33.02cm x 50.03cm)

Paper Thickness

100-350 gsm

Lamination Thickness

1.5, 3, 5 mil

Laminating Modes

Double sided, single sided with anti-curl device with no need for release film, adjustable encapsulation and trim to bleed

Laminating Width

4.4" - 12.9" *custom widths available

Cutting Method

2 automatic setup side slitters and 1 guillotine cutter assembly

Feeding Method

2" vacuum pile feeder

Speed

Variable speeds up to 10 feet per minute

Machine Weight

584lbs (265kg)

Machine Dimensions

64.9" x 24.4" x 43.3" (165cm x 62cm x 110cm)

Electrical

110-130V, 60Hz, 15A

NOTE: Machine performance will vary based on stock weight, type, and specifications of the job being performed.
WARRANTY: 1 year warranty (excludes consumables)

www.graphicwhizard.com

CONTACT US TODAY!

sales@graphicwhizard.com



GW-PT33LSC-SS-082024