

# SP BANDER

Paper or poly band business cards, postcards and brochures with the SP Bander. Banding your work is easy and more economical than boxing or shrink wrapping. The SP Bander comes as a standard tabletop model, with an available optional high capacity stand.

## FEATURES

- Available in either paper or poly rolls
- Adjustable backstops for feeding ease
- LCD readout for operation adjustments
- Adjustable lag time for variable feeding
- Adjustable tension for delicate jobs
- Optional Jumbo roll stand available for high volume users
- Closed arch system for feeding ease and durability
- Quick release to cut and eject the banding in case of misfeeds
- Manual, Foot-pedal, or automatic sensor-driven operation



## SPECIFICATIONS

<b>Minimum Input Size</b>	1.2" x 0.4" (3cm x 1cm)
<b>Maximum Input Size</b>	18" x 7.9" (46cm x 20cm)
<b>Banding Specifications</b>	1.2" (3cm) wide x 100-120 microns (thickness)
<b>Banding Types</b>	Poly film or paper
<b>Banding Roll Size</b>	150 metre (492') length
<b>Banding Speed</b>	20 pieces/minute (operator dependent)
<b>Sealing Method</b>	Thermal sealing (self-welding tape)
<b>Feeding Method</b>	Manual
<b>Tabletop/Floor</b>	Tabletop model (optional stand available shown above)
<b>Controls</b>	Manual, foot pedal, automatic
<b>Machine Weight</b>	Without Stand: 90lbs (41kg) With Stand: 140lbs (63.5kg)
<b>Machine Dimensions</b>	Without Stand: 25"x15"x 20" (63.5cm x 38.1cm x 50.8cm) With Stand: 25"x 15"x50" (63.5cm x 38.1cm x 127cm)
<b>Electrical</b>	110-130V, 60Hz, 15A

NOTE: Machine performance will vary based on stock weight, type, and specifications of the job being performed.  
WARRANTY: 1 year warranty (excludes consumables)

