

StrapPack

Strapping Machine with Brushless DC Motor

Introducing StrapPack's new line of strapping machine, the SQ-800 with brushless DC motor. The SQ-800 provides better efficiency without compromising the reliability of the legendary RQ-8x.

■ Strapping Speed

Standard strapping rate is 1.1 sec = 55 straps/min, even when a tension is applied. The machine is ready to operate in less than 25 seconds, contributing to increased packaging line efficiencies.

■ Even Less Moving Parts, with Self-Lubricating Design

Using the DC motor for the Cam Shaft eliminates the need for clutch, brake, V-belt (A type), FR roller, driven micro-V belt, and back tension. This means less moving parts and less maintenance cost. The self-lubricating design also reduces wear and tear and increases operational life.

■ Less Dusting

At standard speed, the DC motor allows the rollers to run only during feeding and reversing. This reduces strap dust, which in turn, reduces dust build up.

■ Various Tension Setting

The SQ-800 offers different modes of tensioning system which can be selected according to the application requirements. A wide range of tension is available via a digitally controlled tension dial. Tension capability is up to 450 N (46 kgf). Unlike many other machines in the market, tension does not compromise the cycle speed.

■ Quiet

Noise reduction during standby mode lessens the excessive noise pollution in the workplace.

■ Standard Operational Advantages

Adjustable table height for easy integration
Foot bar for hands-free operation
Cycle Counter
Automatic Strap Tail Ejection

■ Other Features

Easy strap loading
Automatic Re-Feed
Anti-Jam Function



SQ-800



Table Height Adjustment is a standard feature.

Standard Specifications

Dimensions	Width	1254 mm	49-3/8 in.
	Height	1403-1508 mm	55-1/4 to 59-3/8 in.
	Depth	609 mm	24 in.
	Weight	149 kg	328 lbs.
Table Height		794-899 mm	31-1/4 to 35-3/8 in.
Package Size	Max.	W 620 x H 480 mm	W 24-1/2 x H 18-7/8 in.
	Min.	W 80 x H 30 mm	W 3-1/8 x H 1-1/8 in.
Joint / Strap		heat seal / polypropylene	heat seal / polypropylene
Strap		5, 6, 9, 12, 15.5 mm	1/4, 3/8, 1/2 in.
Strap Tension		450 N (46 kgf)	101 lbf
Power Supply		100, 120, 220, 230, 240V Single phase 50/60Hz 0.74kVA	

Dimensions and specifications are subject to change without notice.
Modification rights reserved.

© 2018 Strapack

DISTRIBUTED BY:

PACKSOURCE
Systems
Innovation in Packaging Supplies • Machinery • Service • Design

Packsource Systems, Inc.

2158 Union Place, Simi Valley, CA. 93065
Phone 1-800-464-3100 Fax. 1-805-520-7555

Mike Ferrato- Strapping Specialist

mike@packsourcesys.com
www.packsourcesys.com